

Top Primer Sc

Pigmented, filled primer for decorative silicone resin plasters

Areas of application	Primer to match the colour and improve the adhesion of the final coat of silicone-resin plasters. Suitable for interior and exterior applications.	
Product properties	<ul style="list-style-type: none"> ■ Water-vapour permeable ■ Acts as coupling agent ■ Adhesion-improving ■ Absorbency-regulating ■ Reduces the risk of colour variations in the subsequent application of pigmented silicone-resin plasters ■ Surface provides a good grip, since it is filled with quartz ■ Results in optimum and economical application of the decorative plaster 	
Technical data	Binder base	Acrylic-resin dispersion
	Specific gravity	approx. 1,7 g/cm ³
Application instructions	Substrate pre-treatment	<ul style="list-style-type: none"> - All substrates must be sound, even, clean and free from adhesion-reducing residue. - Apply Sub Primer to substrates that need to be stabilised.
	Mixing	Ready for application Can be thinned with 20 % water max.
	Application	<ul style="list-style-type: none"> - Apply by brush, roller or as a spray. - Use short-pile rollers to ensure an even application.
	Consumption	approx. 200 - 250 ml/m ² Determine the exact amount of material required by coating a test area on site.
	Information about the weather	The temperature must not fall below + 5 °C during application and drying.
	Drying time	approx. 2 - 6 hours Dependent on temperature and relative humidity
	Cleaning of tools	With water while product is still fresh
	Application by machine	Please ask for our special information sheet on machine application.

Packaging	Article number	06129
	Packaging unit	PP tub 15 l
	Colour	Natural white and pigmented
Other information	Transport	Not a hazardous product
	Storage	Minimum storage life of 1 year if kept cool, protected against frost and in the original sealed packaging.
	Information on safety	We will be pleased to provide the EC safety data sheet on request.

alsecco GmbH & Co. KG

Kupferstraße 50

D-36208 Wildeck

Telefon 03 69 22 / 88-0

Telefax 03 69 22 / 88-330

Internet: www.alsecco.de

The above information is based on many years of experience and tests and is provided by us to the best of our knowledge. Such information applies in addition to our application guidelines. However, we cannot accept any responsibility for the correctness of our recommendations on account of wide variety of substrates and of on-site conditions and applications which are outside our control. Any recommendations provided by our employees and deviating from these documents must be given in writing. We reserve right to make any changes on account of technical progress or building regulations. Your technical advisor will be pleased to provide the relevant product data sheets.

PD 0269/1099